

PRODUCT SPECIFICATIONS FOR 289D3

		US	Metric
Gross Power - SAE J1995	74.3 HP		
Net Power - SAE 1349	72.9 HP		
Displacement	203 in³		
Bore	3.7 in		
Stroke	4.7 in		
Net Power	72.9 HP		
Note	Net power advertised is the power available at the flywheel when the engine is equipped with alternator, air cleaner, muffler/aftertreatment and cooling fan.		
Engine Model	Cat C3.3B DIT (turbo)		
Peak Torque - 1,500 rpm - SAE J1995	195 ft·lbf		
Net Power - ISO 9249	73.7 HP		
Rated Operating Capacities - 35% Tipping Load	2890 lb		
Tipping Load	8255 lb		
Breakout Force - Tilt Cylinder	7291 lb		
Rated Operating	4370 lb		

**Capacity with
Optional
Counterweight**

**Rated Operating
Capacities - 50%
Tipping Load** 4130 lb

**Ground Pressure -
With 450 mm/17.7 in
Track** 4.7 psi

**Ground Contact Area -
With 450 mm/17.7 in
Track** 2272 in²

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, two speed, OROPS, 2036 mm (80 in) low profile bucket, 450 mm (17.7 in) tracks, dual flange front idler/single flange rear idler, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

**Operating
Weight** 10688 lb

Note Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, two speed, OROPS, 2036 mm (80 in) low profile bucket, 450 mm (17.7 in) tracks, dual flange front idler/single flange rear idler, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).

**Length - Track on
Ground** 64.2 in

**Overall Length -
Track** 83.8 in

Height - Top of Cab 83.2 in

Ground Clearance	8.9 in
Departure Angle	33°
Maximum Dump Angle	51°
Clearance at Maximum Lift and Dump	94 in
Turning Radius from Center - Machine Rear	70.7 in
Length - Without Bucket	117.9 in
Maximum Reach - With Arms Parallel to Ground	50 in
Turning Radius from Center - Bucket	88.8 in
Bucket Pin Height - Carry Position	7.5 in
Turning Radius from Center - Coupler	55.5 in
Bucket Pin Height - Maximum Lift	125.1 in
Reach - Maximum Lift/Dump	30 in
Length - With Bucket on Ground	146.2 in
Maximum Overall	158.1 in

Maximum Overall Height	150.1 in
Rack Back Angle - Maximum Height	84°
Bucket Pin Reach - Maximum Lift	14.5 in
Vehicle Width (450 mm/17.7 in tracks)	78 in
Note	Operating Weight, Operating Specifications and Dimensions all based on 75 kg (165 lb) operator, all fluids, two speed, OROPS, 2036 mm (80 in) low profile bucket, 450 mm (17.7 in) tracks, dual flange front idler/single flange rear idler, standard flow hydraulics, mechanical suspension seat, no optional counterweights and manual quick coupler (unless otherwise noted).
Hydraulic Flow - Standard - Hydraulic Power (Calculated)	44 HP
Hydraulic Flow - High Flow XPS - Maximum Loader Hydraulic Pressure	4061 psi
Hydraulic Flow - Standard - Loader Hydraulic Flow	23 psi
Hydraulic Flow - High Flow XPS - Hydraulic Power (Calculated)	76 HP
Hydraulic Flow - Standard - Loader Hydraulic Pressure	3335 psi
Hydraulic Flow - High Flow XPS - Maximum Loader Hydraulic Flow	32 gal/min
ROPS	ISO 3471:2008
FOPS	ISO 3449:2005 Level I
Travel Speed - Forward or Reverse - Two Speed	8.3 mile/h

Travel Speed - Forward or Reverse - One Speed

4.5 mile/h

Cooling System 3.7 gal (US)**Engine Crankcase** 3 gal (US)**Fuel Tank** 27.7 gal (US)**Hydraulic System** 13.7 gal (US)**Hydraulic Tank** 10.3 gal (US)

Air Conditioning The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 1 kg of refrigerant which has a CO2 equivalent of 1.430 metric tonnes.

Note (2) **The declared dynamic operator sound pressure levels per ISO 6396:2008. The measurements were conducted with the cab doors and windows closed and at 70% of the maximum engine cooling fan speed. The sound level may vary at different engine cooling fan speeds.

Outside Cab*** 103 dB(A)**Inside Cab**** 83 dB(A)

Note (3) ***The labeled sound power level for the CE marked configurations when measured according to the test procedure and conditions specified in 2000/14/EC.

Note (1) Cab and Rollover Protective Structures (ROPS) are standard in North America and Europe.

289D3 STANDARD EQUIPMENT

ELECTRICAL

12 volt Electrical System

80 ampere Alternator

Ignition Key Start/Stop Switch

Lights: Gauge Backlighting, Two Rear Tail Lights, Two Rear Halogen Working Lights, Two Adjustable Front Halogen Lights, Dome Light

Backup Alarm

Heavy Duty Battery, 850 CCA

OPERATOR ENVIRONMENT

Advanced Display with Rearview Camera: Full Color, 127 mm (5 in) LCD screen; Advanced Multi-operator Security System; On-screen Adjustments for Implement Response, Hystat Response and Creep Control

Gauges: Fuel Level, Hour Meter

Operator Warning System Indicators: Air Filter Restriction, Alternator Output, Armrest Raised/Operator Out of Seat, Engine Coolant Temperature, Engine Oil Pressure, Glow Plug Activation, Hydraulic Filter Restriction, Hydraulic Oil Temperature, Park Brake Engaged, Engine Emission System

Adjustable Vinyl Seat

Fold In Ergonomic Contoured Armrest

Control Interlock System, when operator leaves seat or armrest raised: Hydraulic System Disables, Hydrostatic Transmission Disables, Parking Brake Engages

ROPS Cab, Open, Tilt Up

FOPS, Level I

Top and Rear Windows

Floor Mat

Interior Rearview Mirror

12 volt Electric Socket

Horn

Hand (Dial) Throttle, Electronic

Adjustable Joystick Controls

Anti-theft Security System with 6-button Keypad

Storage Compartment with Netting

POWER TRAIN

Cat C3.3B, Turbo Diesel Engine, Meeting Tier 4 Final and Stage V Emission Standards

Air Cleaner, Dual Element, Radial Seal

S-O-SSM Sampling Valve, Hydraulic Oil

Filters, Cartridge-type, Hydraulic

Filters, Canister-type, Fuel and Water Separator

Radiator/Hydraulic Oil Cooler (side-by-side)

Spring Applied, Hydraulically Released, Wet Multi Disc Parking Brakes

Hydrostatic Transmission, Two Speed Travel

Suspension – Independent Torsion Axles (4)

OTHER

Engine Enclosure, Lockable

Extended Life Antifreeze, -37° C (-34° F)

Machine Tie Down Points (6)

Support, Lift Arm

Hydraulic Oil Level Sight Gauge

Radiator Coolant Level Sight Gauge

Radiator, Expansion Bottle

Cat ToughGuard™ Hose

Auxiliary, Hydraulics, Continuous Flow

Heavy Duty, Flat Faced Quick Disconnects with Integrated Pressure Release

Split D-Ring to Route Work Tool Hoses Along Side of Left Lift Arm

Electrical Outlet, Beacon

Belly Pan Cleanout

Variable Speed Demand Fan

Product Link™ PL243, Cellular

MANDATORY EQUIPMENT

Hydraulics, Standard or High Flow XPS

Quick Coupler, Mechanical or Powered

High Visibility Seat Belt, 50 mm (2 in) or 75 mm (3 in)

Steel Imbed Rubber Track – 450 mm (17.7 in)

Dual Flange Front Idler/Single Flange Rear Idler or Triple Flange Front/Rear Idlers

PERFORMANCE PACKAGES:

- Performance Package H1: Standard Flow Hydraulics (No Self Level)
- Performance Package H2: Standard Flow, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)
- Performance Package H3: High Flow XPS, Dual Direction Electronic Self Level (Raise and Lower), Work Tool Return to Dig, Work Tool Positioner, and Electronic Snubbing (Raise and Lower)

COMFORT PACKAGES:

- Open ROPS (C0): Static Seat (No Foot Throttle, Headliner, Heater or Door)
- Open ROPS (C1): Foot Throttle, Headliner, Cup Holder, and choice of Seat (Mechanical Suspension or High Back, Heated, Air Ride Seat) (No Heater or Door)
- Enclosed ROPS with Heater (C2): Foot Throttle, Headliner, Heater and Defroster, Side Windows, Cup Holder, Radio Ready, choice of Seat (Mechanical Suspension or High Back, Heated, Air Ride Seat) and Door (Glass or Polycarbonate)
- Enclosed ROPS with A/C (C3): C2 + Air Conditioner

289D3 OPTIONAL EQUIPMENT

OPTIONAL EQUIPMENT

Hand-Foot Style Controls

External Counterweights

Beacon, Rotating

Engine Block Heater – 120V

Oil, Hydraulic, Cold Operation

Paint, Custom

Heavy Duty Battery, 1,000 CCA

Product Link PL641, Cellular

Ride Control

Bluetooth® Radio with Microphone (AM/FM/Weather Band Receiver with USB and Auxiliary Input Jack)