

Mini Track Loaders / MT100 Mini Track Loader

MT100 Loader Specifications & Options

Review complete specs for the MT100 mini track loader and see how it stacks up to other models.

Standard
 Optional
 N/A Not Applicable

Units **US**

Bobcat MT100

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	55 in ³
Number of Cylinders	3
Horsepower	24.8 hp

Performance

Rated Operating Capacity (ISO)	1,000 lb
ROC (ISO) with Standard Counterweight - Undercarriage Position	n/a
ROC (ISO) with Standard Counterweight - Rear Upright Position	n/a
Carry Position ROC with Standard Counterweight -UnderCarriage Position	1,300 lb
Carry Position ROC with Standard Counterweight - Rear Upright Position	n/a
Tipping Load	2898 lb
Operating Weight	3390 lb
Ground Pressure (Rubber)	5.25 psi
Travel Speed	4.1 mph
Travel Speed - Reverse	2.9 mph

Capacities

Fuel Tank	7 gal
-----------	-------

Hydraulic System

Pump Capacity	12 gal/min
System Relief @ Quick Couplers	2,900 psi
Auxiliary Std Flow	12 gal/min

Dimension

Length	106.2 in
Width	35.6 in
Height	54.6 in
Height to Bucket Hinge Pin	80.9 in
Length of track on ground	41.4 in
Reach @ Maximum Height	18.6 in