

Compact Track Loaders / T770 Compact Track Loader

T770 Loader Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Units **US**

Configuration	Bobcat T770	
	Standard	Roller Suspension Option
Emissions Tier (EPA)		Tier 4
Engine Cooling		Liquid
Engine Fuel		Diesel
Horsepower		92 hp
Turbocharged Engine		<input checked="" type="checkbox"/>

Performance

Rated Operating Capacity (ISO)	3,475 lb
Operating Capacity (50% of Tip)	4960 lb
Tipping Load	9929 lb
Operating Weight	10515 lb
Travel Speed	6.6 mph
Travel Speed (2-speed option)	10.7 mph
Ground Pressure (Rubber)	4.2 psi

Capacities

Fuel Tank	43.8 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	23 gal/min
Auxiliary High Flow	36.6 gal/min

Dimension

Length	141.6 in
Length without Attachment	114.3 in
Length with Standard Bucket	141.6 in
Width	78 in
Width (with bucket)	80 in
Height	81.3 in
Height with Operator Cab	81.3 in
Height to Bucket Hinge Pin	131.4 in
Reach @ Maximum Height	35.2 in
Turning Radius	88 in
Length of track on ground	63.7 in
Track Width	17.7 in

Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	<input type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	<input checked="" type="checkbox"/>
Ride Control	<input checked="" type="checkbox"/>
Horn	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.