

T66 Key Specification

Rated Operating Capacity (ISO)

2,450 lb

Operating Weight

8927 lb

Ground Pressure (Rubber)

5.9 psi

Auxiliary Std Flow

17.6 gal/min

Auxiliary High Flow

26.9 gal/min

Engine

Emissions Tier (EPA)

Tier 4

Engine Cooling

Liquid

Engine Fuel

Diesel

Horsepower

74 hp

Turbocharged Engine

yes

Performance

Rated Operating Capacity (ISO)

2,450 lb

Operating Capacity (50% of Tip)

3500 lb

Tipping Load

7000 lb

Operating Weight

8927 lb

Travel Speed

7.2 mph

Travel Speed (2-speed option)

10.2 mph

Ground Pressure (Rubber)

5.9 psi

Capacities

Fuel Tank

28.3 gal

Hydraulic System

System Relief @ Quick Couplers

3,500 psi

Auxiliary Std Flow

17.6 gal/min

Auxiliary High Flow

26.9 gal/min

Dimension

Length

134.9 in

Length without Attachment

107 in

Length with Standard Bucket

134.9 in

Width

67 in

Width (with bucket)

68 in

Height

80.5 in

Height with Operator Cab

80.5 in

Height to Bucket Hinge Pin

120 in

Reach @ Maximum Height

36.7 in

Turning Radius

81.5 in

Length of track on ground

54.3 in

Track Width

12.6 in

Track Width - Optional

15.7 in